



## Flat TPS Cables – Non-Migratory

**Application:** This cable is used for residential and light to medium commercial construction. The insulation and sheathing material is non-Migratory and suitable for use where cables are in contact with Polystyrene, ABS, Polycarbonate and Acrylic.

**Conductor:** Plain Annealed Copper

**Insulation:** V-90HT

**Sheath:** Non-Migratory

**Sheath Colour:** Purple

**Voltage:** 450/750V

**Temp.:** -50°C to 90°C

**Standards:** AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808

**Greenstar:** Approved

**Drum Sizes:** 100m, 500m

| ELECTRA<br>Part Number | SIZE | CORES | INSULATION<br>Thickness | SHEATH<br>Thickness | O.D.       |
|------------------------|------|-------|-------------------------|---------------------|------------|
| SRF3015VHT             | 1.5  | 2C+E  | 0.6                     | 0.9                 | 10.0 x 4.6 |
| SRF3025VHT             | 2.5  | 2C+E  | 0.7                     | 1.0                 | 12.4 x 5.5 |
| SRF3040VHT             | 4    | 2C+E  | 1                       | 1.1                 | 14.0 x 6.5 |
| SRF3060VHT             | 6    | 2C+E  | 0.8                     | 1.1                 | 15.2 x 7.1 |

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm.*

## Flat TPS Cables – Non-Migratory (LSZH)

**Application:** This cable is used for residential and light to medium commercial construction. The insulation and sheathing material is non-Migratory and suitable for use where cables are in contact with Polystyrene, ABS, Polycarbonate and Acrylic.

**Conductor:** Plain Annealed Copper

**Insulation:** X-HF-90 LSZH 90°C

**Sheath:** X-HF-90 LSZH 90°C

**Sheath Colour:** Purple

**Voltage:** 450/750V

**Temp.:** -50°C to 90°C

**Standards:** AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808

**Greenstar:** Approved

**Drum Sizes:** 100m

| ELECTRA<br>Part Number | SIZE | CORES | INSULATION<br>Thickness | SHEATH<br>Thickness | O.D.       |
|------------------------|------|-------|-------------------------|---------------------|------------|
| SRF3015XLS             | 1.5  | 2C+E  | 0.6                     | 0.9                 | 10.0 x 4.6 |
| SRF3025XLS             | 2.5  | 2C+E  | 0.7                     | 1.0                 | 12.4 x 5.5 |

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm.*

[electracables.com.au](http://electracables.com.au)

**SYDNEY**  
**(02) 8786 5200**

**MELBOURNE**  
**(03) 9706 6819**

**BRISBANE**  
**(07) 3386 9800**

**PERTH**  
**(08) 9454 2628**

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38