



Flat TPS Cables – Low Smoke Zero Halogen

Application:	Easy-peel sheath for general wiring. This cable is used for residential and light commercial construction. Installation is usual where the installation is not subject to mechanical damage. Commonly used also for Festoon Systems
Conductor:	Plain Annealed Copper
Insulation:	X-HF-90 LSZH
Sheath:	X-HF-90 LSZH
Voltage:	450/750V
Temp.:	90° C
Standards:	AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808
Greenstar:	Approved
Drum Sizes:	100m, 500m

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thcikness	O.D.
SRF2015AVLS	1.5	2 (Active)	0.6	0.9	7.2 x 4.6
SRF2025AVLS	2.5	2 (Active)	0.7	1.0	8.9 x 5.5
SRF2040AVLS	4	2 (Active)	0.8	1.1	10.6 x 6.5
SRF2060AVLS	6	2 (Active)	0.8	1.1	11.7 x 7.1
SRF3015VLS	1.5	2C+E	0.6	0.9	10.0 x 4.6
SRF3025VLS	2.5	2C+E	0.7	1.0	12.4 x 5.5
SRF3040VLS	4	2C+E	0.8	1.1	14.0 x 6.5
SRF3060VLS	6	2C+E	0.8	1.1	15.2 x 7.1

**Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm.*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38