



Orange Circular Cables (0.6/1kV)

Application:	For mains, sub-mains, and sub-circuits. Unenclosed, enclosed in conduit, direct buried or underground ducts for buildings and industrial projects where the cable is not subject to mechanical damage. Suitable for glanding.
Conductor:	Plain Annealed Copper
Insulation:	V90 PVC
Sheath:	5V-90 PVC
Voltage:	600V-1000V (0.6/1kV)
Temp:	90°C
Standards:	AS/NZS 5000.1, AS/NZS 1125, AS/NZS 3808
Greenstar:	Approved
Drum Sizes:	100m, 500m

2 x Core + Earth

ELECTRA Part Number	SIZE	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
SRC2015E	1.5	0.8	1.8	10.3
SRC2025E	2.5	0.8	1.8	11.4
SRC2040E	4	1.0	1.8	13.0
SRC2060E	6	1.0	1.8	14.0

*O.D. $\pm 10\%$ = mm *All above = mm, Core Colours: RED, BLACK, G/Y

3 x Core + Earth

ELECTRA Part Number	SIZE	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
SRC3015E	1.5	0.8	1.8	11.0
SRC3025E	2.5	0.8	1.8	12.6
SRC3040E	4	1.0	1.8	14.5
SRC3060E	6	1.0	1.8	15.8

*O.D. $\pm 10\%$ = mm *All above = mm. Core Colours: RED, WHITE, BLUE, G/Y

4 x Core + Earth

ELECTRA Part Number	SIZE	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
SRC4015E	1.5	0.8	1.8	11.8
SRC4025E	2.5	0.8	1.8	13.5
SRC4040E	4	1.0	1.8	15.8
SRC4060E	6	1.0	1.8	17.0

*O.D. $\pm 10\%$ = mm *All above = mm. Core Colours: RED, WHITE, BLUE, BLACK, G/Y

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38