

Flexible Building Wire

- Application:

Used for enclosed wiring where 0.6/1kV insulation is required at a higher operating temperature in control panels and general electrical appliances. Suitable for swing-out panels.
- Conductor:

Tinned Copper
- Insulation:

V90HT PVC
- Temp:

105°C
- Voltage:

600/1000V (0.6/1kV)
- Standards:

AS/NZS 3191 (up to 4mm²), AS/NZS 5000.1 (6-35mm²), AS/NZS 1125, AS/NZS 3808, RoHS meets IEC6231.1:2008 & 2011/65/EU
- Greenstar:

Approved
- Drum Sizes:

100m

ELECTRA Part Number	SIZE	INSULATION Thickness	O.D.	COLOURS
F1005VT	0.5	0.8	2.6	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1075VT	0.75	0.8	2.8	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1010VT	1	0.8	3	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1015VT	1.5	0.8	3.1	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1025VT	2.5	0.8	3.6	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1040VT	4	1.0	4.6	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, G/Y
F1060VT	6	1.0	5.1	Black, Red, Blue, White, Green/Yellow
F1100VT	10	1.0	6.1	Black, Red, Blue, White, Green/Yellow
F1160VT	16	1.0	7.1	Black, Red, Blue, White, Green/Yellow
F1250VT	25	1.2	8.9	Black, Red, Blue, White, Green/Yellow

**Size = mm², O.D. ± 10%, Insulation Thickness & O.D. = mm.*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38