

# Aerial Bundle Cables (ABC)

Application: For aerial reticulation to residential and rural areas where reliability, safety, and low installation costs are required. ABC Cables reduce bushfire hazard and environments pertaining to frequent tree lopping in uncleared areas. Incorporates UV stabilisation for continuous exposure to sunlight.

Conductor: Aluminium

Insulation: X-90 XLPE Black

Voltage: 600V/1000V (0.6/1kV)

Temp: 90°C

Standards: AS/NZS 3560:1

Greenstar: Approved

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	O.D.	MIN BEND Radius	DRUM SIZES
ABC2250	25	2	1.3	17.2	110	100, 300, 500m
ABC4250	25	4	1.3	20.8	135	100, 200, 500m
ABC4500	50	4	2	27.0	160	100, CUSTOM
ABC4950	95	4	2	36.0	345	500, CUSTOM

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Min. Bend Radius, O.D. = mm.*

*\*All cables can be custom cut to length*

electracables.com.au

SYDNEY  
(02) 8786 5200

MELBOURNE  
(03) 9706 6819

BRISBANE  
(07) 3386 9800

PERTH  
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38