

Aluminium Earth Cables

Conductor: Aluminium
Insulation: PVC V-90
Sheath: PVC V-90
Sheath Colour: Green/Yellow
Voltage: 600V/1000V (0.6/1kV)
Standards: AS/NZS 5000.1, AS/NZS 3808 (PVC), AS/NZS 1125 Class 2
Temp: Operating 90°C – When not exposed to mechanical deformation.

ELECTRA Part Number	SIZE	INSULATION RADIUS	MIN. BENDING RADIUS	O.D.
ALSR1100	10	1.0	37	6.0
ALSR1160	16	1.0	56	7.0
ALSR1250	25	1.2	70	8.8
ALSR1350	35	1.2	79	9.9
ALSR1500	50	1.4	92	11.6
ALSR1700	75	1.4	106	13.3
ALSR1950	90	1.6	124	15.5
ALSR11200	120	1.6	137	17.1

**Size = mm², O.D. ± 10%, Insulation Thickness, O.D. & Bend Radius = mm.*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38