



Control Cables

Application: Transmission cables requiring mechanical motion. Used to relay the required signal/action to a particular control point. Control Cables are the backbone of automated systems.

Conductor: Plain Annealed Copper

Insulation: PVC V90

Core Colours: White + Green/Yellow

Sheath: PVC V90

Voltage: 600/1000V (0.6/1kV)

Temp: 90°C

Standards: AS/NZS 5000.1, AS/NZS 1125

Greenstar: Approved

Control Cables 1.5mm²

ELECTRA Part Number	CORES	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
SRCC2015E	2C+E	0.8, 0.6E	1.8	10.3
SRCC3015E	3C+E	0.8, 0.6E	1.8	11.0
SRCC4015E	4C+E	0.8, 0.6E	1.8	11.8
SRC5015E	5C+E	0.8, 0.6E	1.8	13.0
SRC6015E	6C+E	0.8, 0.6E	1.8	13.0
SRC8015E	8C+E	0.8, 0.6E	1.8	15.2
SRC10015E	10C+E	0.8, 0.6E	1.8	16.5
SRC12015E	12C+E	0.8, 0.6E	1.8	17.4
SRC15015E	15C+E	0.8, 0.6E	1.8	19.2
SRC16015E	16C+E	0.8, 0.6E	1.8	20.2
SRC20015E	20C+E	0.8, 0.6E	1.8	22.9
SRC25015E	25C+E	0.8, 0.6E	1.8	24.5
SRC30015E	30C+E	0.8, 0.6E	1.9	29.0
SRC40015E	40C+E	0.8, 0.6E	1.9	30.2
SRC50015E	50C+E	0.8, 0.6E	1.9	35.0

*O.D. ± 10% = mm. Insulation Thickness, Sheath Thickness & O.D. = mm

** For 'Black' sheath, please place 'X' before 'Electra Part Number'.

Control Cables 2.5mm²

ELECTRA Part Number	CORES	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
SRCC2025E	2C+E	0.8, 0.7E	1.8	11.4
SRCC3025E	3C+E	0.8, 0.7E	1.8	12.6
SRCC4025E	4C+E	0.8, 0.7E	1.8	13.5
SRC5025E	5C+E	0.8, 0.7E	1.8	14.6
SRC6025E	6C+E	0.8, 0.7E	1.8	14.6
SRC8025E	8C+E	0.8, 0.7E	1.8	17.3
SRC10025E	10C+E	0.8, 0.7E	1.8	18.9
SRC12025E	12C+E	0.8, 0.7E	1.8	20.0
SRC15025E	15C+E	0.8, 0.7E	1.8	21.9
SRC16025E	16C+E	0.8, 0.7E	1.8	22.8
SRC20025E	20C+E	0.8, 0.7E	1.8	25.9
SRC25025E	25C+E	0.8, 0.7E	1.8	25.9
SRC30025E	30C+E	0.8, 0.7E	1.8	28.0
SRC40025E	40C+E	0.8, 0.7E	2.0	33.0
SRC50025E	50C+E	0.8, 0.7E	2.0	35.0

*O.D. ± 10% = mm. Insulation Thickness, Sheath Thickness & O.D. = mm

** For 'Black' sheath, please place 'X' before 'Electra Part Number'.

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38