

Flexible Control Cables

Application: Flexible Transmission cables requiring mechanical motion. Used to relay the required signal/action to a particular control point. Control Cables are the backbone of automated systems.

Conductor: Plain Annealed Copper

Insulation: PVC V-90HT

Core Colours: Black Numbered Cores + Green/Yellow

Sheath: Flame Retardant PVC V90

Sheath Colour: Grey

Voltage: 300/500V

Temp: 90°C

Standards: AS/NZS 5000.1, IEC 60227-7:2003, AS/NZS 1125, AS/NZS 3808

Greenstar: Approved

ELECTRA Part Number	SIZE	INSULATION THICKNESS	SHEATH THICKNESS	O.D.
F6075E	0.75	0.6	1.0	10.0
F11075E	0.75	0.7	1.2	15.0
F4010E	1	0.6	0.9	8.5
F6010E	1	0.6	1.0	9.5
F8010E	1	0.6	1.2	12.4
F11010E	1	0.6	1.2	15.0
F16010E	1	0.6	1.2	14.9
F4015E	1.5	0.7	1.1	10.2
F6015E	1.5	0.7	1.2	11.4
F8015E	1.5	0.7	1.3	14.5
F11015E	1.5	0.7	1.3	15.0
F16015E	1.5	0.7	1.3	17.5
F6025E	2.5	0.8	1.3	13.5
F11025E	2.5	0.8	1.5	18.0

*Size = mm². O.D. ± 10%. Insulation Thickness, Sheath Thickness & O.D. = mm

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38