

Welding Cables

Application: For use with arc welding equipment rated in accordance with AS1966. Suitable for glanding.
Conductor: Plain Annealed Copper
Insulation: Nitrile-Butadiene PVC Copolymer (TP-90 RoHS)
Sheath: Nitrile-Butadiene PVC Copolymer (TP-90 RoHS) - Orange
Standards: AS1995
Greenstar: Approved

ELECTRA Part Number	SIZE	INSULATION Thickness	SHEATH Thcikness	O.D.
ZW10	10.0	0.9	1.1	8.2
ZW16	16.0	0.9	1.1	9.3
ZW25	25	0.9	1.1	10.7
ZW35	35	0.9	1.1	11.9
ZW50	50	1.0	1.2	13.6
ZW70	70	1.1	1.3	15.6
ZW95	95	1.2	1.4	18.2
ZW120	120	1.4	1.4	20.4

**Size = mm², O.D. ± 10%, insulation Thickness, Sheath Thickness and O.D. = mm*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38