

Fire Rated Control Cables

Application: Flexible Halogen Free, Low Smoke, Low Toxic, Flame Retardant Cable. Used for Control applications within the fire protection industry. Independently tested and certified to AS/NZS 3013:1995-Category WS52W, IEC 60332-3, BS6387, AS/NZS 4507:2006

Norm. Operating Temp.: 110°C

Conductor: Plain Annealed Copper (Class 5 of IEC 60228)

Barrier: Mica Glass Tape

Insulation: X-HF-110

Insulation Colour: White Cores + Green / Yellow Earth

Sheath: HF-110-TP - Orange

Voltage: 600/1000V (0.6/1kV)

Standards: AS/NZS 3013-Category WS52W, IEC 60332-3 and BS6387, AS/NZS IEC 60754.1, AS/NZS 4507:2006, AS/NZS 5000.1, AS/NZS 3808.

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	O.D.
FRC6015E	1.5	6+E	0.7 + 0.7E	1.8	16.5
FRC8015E	1.5	8+E	0.7 + 0.7E	1.8	19.0
FRC6025E	2.5	6+E	0.7 + 0.7E	1.8	17.6

**Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness, O.D. & Bend Radius = mm, Weight = kg/km.
Other cable combinations available.*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38