

Battery Cables

Application: General purpose cables for battery and starter motors.
 Core Colours: Red, Black
 Packing Length: 30m, 100m
 Greenstar: Approved

ELECTRA Part Number	Nom. Area mm ²	O.D.	Insulation Thickness	Cont. Duty AMPS **
EBS8	7	5.60	0.9	55
EBS6	15	7.80	1.1	52
EBS4	20	8.80	1.1	100
EBS3	23	10.20	1.1	120
EBS2	33	11.50	1.7	130
EBS1	41	12.50	1.7	150
EBS0	50	13.50	1.7	180
EBS00	65	15.20	1.7	210
EBS000	83	17.20	2.0	240
EBS0000	100	18.40	2.0	270
EBS821	2 x 7	7.2 x 15	0.9	55
EBS621	2 x 15	9.4 x 19.8	1.1	85

* O.D. \pm 10%, O.D., Insulation Thickness = mm

** Duty amps specified are nominal only at 60% duty cycle over 5 minutes; Derating factors will have to be applied to certain installations. For intermittent duty, the battery cable will carry 200% of its rated ampere capacity.

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38