



Intrinsically Safe Instrumentation Cables

Application: Internal and external inter-connections of electronic apparatus such as computers, intercoms, signalling and alarm systems.

Conductor: Annealed Copper Wire

Insulation: PVC V-90HT

Core Colours: Light Blue and White

Voltage: 0.6/1kV

Screen: Overall Aluminium Tape Screen and Polyester Mylar Tape Lapping

Drain Wire: Tinned Copper 7/0.25

Sheath: PVC 5V-90

Sheath Colour: Light Blue

Standards: AS1125 (Conductor), AS/NZS 3808 (PVC)

Greenstar: Approved

ELECTRA Part Number	PAIRS	SIZE	Sheath Thickness	O.D.
EAS7301PHV	1	0.55	1.8	8.7
EAS7501PHV	1	1.50	1.8	9.9
EAS7302PHV	2	0.55	1.8	12.0
EAS7502PHV	2	1.5	1.8	13.9

*O.D. $\pm 10\%$ = mm *Size = mm²

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38