

DETONATOR CABLES

Application: For the interconnection of detonators and related shot firing equipment.
Conductor: Bare Copper
Insulation: PVC V-75
Colour: Green / Yellow
Standards: AS/NZS 3808
Notes: Two Bare Copper Conductors twisted and striped Shot Fire Cable.

ELECTRA Part Number	CORES	STRANDS	INSULATION Thickness	CABLE Colours	O.D.
DET7202	2	7/0.20	0.25	White / White	2.2
DET10502	2	1/0.50	0.4	Red / White	2.6
DET10612	2	1/0.61	0.4	Red / Green	2.8
DET10712	2	1/0.71	0.4	Red / White Yellow / Yellow	3.0
DET70502	2	7/0.50	0.8	Red / White	6.15

**Size = mm², O.D. ± 10%, Insulation Thickness, Strands, & O.D. = mm.*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38