ELECTRA CABLES

Fire Rated 110° Multicore (No Earth)

Application: Flexible multi-core halogen free, low smoke, low toxicity, non-corrosive emission, flame retardant cables for the Fire Protection industry.

Conductor: Plain Annealed Copper Wire Class 5

Voltage: 450/750V

Barrier: Mica Glass Tape (WS52W)

Insulation: X-HF-110

Sheath: HFS-110-TP

Sheath Colour: Red or Red with White Stripe

Core Colours: 2 x Cores: Red, White

3 x Cores: Red, White, Blue

4 x Cores: Red, White, Blue, Black

6 & 8 Cores: White

Standards: AS/NZS 3013:2005, AS/NZS 5000.2 – Category WS52W, IEC 60332-3 and BS6387

Fire Rating: WS52W

Water Rating: WS5XW

ELECTRA Part Number	SIZE	CORES	O.D.	INSULATION Thickness	SHEATH Thickness
FRC2075	0.75	2	9.4	0.6	1.2
FRC2010	1.00	2	9.5	0.6	1.2
FRC2015	1.50	2	10.3	0.6	1.3
FRC3075	0.75	3	10.1	0.6	1.3
FRC4075	0.75	4	11.0	0.6	1.3
FRC4015	1.50	4	11.9	0.6	1.3
FRC6075	0.75	6	13.2	0.6	1.4
FRC8075	0.75	8	14.7	0.6	1.4

*Size = mm², O.D. ± 10%, O.D., Insulation thickness and Sheath Thickness = mm

Part Number	Core Colours	Sheath Colour	Drum Sizes
FRC2075-RED	Red, White	Red (RED)	100m, 250m, 500m - Custom Cuts Available
FRC2075-RW	Red, White	Red c/w White Trace (RW)	100m, 250m, 500m - Custom Cuts Available
FRC2010-RED	Red, White	Red (RED)	100m, 250m, 500m - Custom Cuts Available
FRC2010-RW	Red White	Red c/w White Trace (RW)	100m, 250m, 500m - Custom Cuts Available
FRC2015	Red, White	Red (RED)	100m, 250m, 500m - Custom Cuts Available
FRC2015-RW	Red, White	Red c/w White Trace (RW)	100m, 250m, 500m - Custom Cuts Available
FRC3075	Red, White, Blue	Red (RED)	500m - Custom Cuts Available
FRC4075	Red, White, Blue, Black	Red (RED)	500m - Custom Cuts Available
FRC4015	Red, White, Blue, Black	Red (RED)	100m, 250m, 500m - Custom Cuts Available
FRC6075 & FRC8075	White	Red (RED)	100m, 500m - Custom Cuts Available

electracables.com.au

SYDNEY (02) 8786 5200 | **MELBOURNE** (03) 9706 6819 | **BRISBANE** (07) 3386 9800 | **PERTH** (08) 9454 2628

SM181024